

The 9000 Mobile Brake Tester offers as standard all the features required to carry out commercial brake testing. These include Roller Lock, Soft Start, bi-directional, 4WD, automatic weighing, remote control, 2.2KW, 4.8KW, 11KW & 15KW Motor-gearboxes, robust work station, PC package complete with 23" Monitor, Tablet operation and the latest DVSA software.

SPECIFICATION

- Size: 4330 x 1210 x 196mm
- Max. Axle Weight: 20,000 Tonne
- Weight: 2 x 450kg
- Roller size: 1100 x 160mm
- Roller separation: 430mm
- Test Speed: 2.12km/h
- Relative humidity: <95%
- Test speed: 2.5Km/h
- Friction Coefficient: Dry > 0,8
Humid > 0,6
- Measurement range: 0 - 4,000kg
- Power Supply 3 x 400V - 50/60 Hz
- Working Conditions: Temp -5+ +40°C

FEATURES:

- DVSA approved 'approval pending'
- GEA approved
- Motors: 2 x 2.2KW, 4.8KW, 11KW or 15KW
- Guaranteed to get out rollers first time every time, safely
- Bi — directional
- 4x4 Programme
- Automatic weighing system
- 18/20t axle weight
- Soft start operation
- Emergency stop button
- Full PC package as standard
- One-man operation/Tablet

